Package: aiRthermo (via r-universe)

November 11, 2026

Type Package

Title Atmospheric Thermodynamics and Visualization

Version 1.2.2

Date 2025-05-05

Author Jon Sáenz [aut, cph] (ORCID: <https://orcid.org/0000-0002-5920-7570>), Santos J. González-Rojí [aut, cre, cph] (ORCID: <https://orcid.org/0000-0003-4737-0984>), Sheila Carreno-Madinabeitia [aut, cph] (ORCID: <https://orcid.org/0000-0003-4625-6178>), Gabriel Ibarra-Berastegi [ctb, cph] (ORCID: <https://orcid.org/0000-0001-8681-3755>)

Maintainer Santos J. González-Rojí <santosjose.gonzalez@ehu.eus>

Description Deals with many computations related to the thermodynamics of atmospheric processes. It includes many functions designed to consider the density of air with varying degrees of water vapour in it, saturation pressures and mixing ratios, conversion of moisture indices, computation of atmospheric states of parcels subject to dry or pseudoadiabatic vertical evolutions and atmospheric instability indices that are routinely used for operational weather forecasts or meteorological diagnostics.

Depends R (>= 3.5.0)

License GPL-3

Encoding UTF-8

NeedsCompilation yes

Repository https://sjgonzalezroji.r-universe.dev

Date/Publication 2025-05-07 11:30:02 UTC

RemoteUrl https://github.com/cran/aiRthermo

RemoteRef HEAD

RemoteSha 10cd3a5a64cdf0e4cd82d284542fb3e191010f3f

Contents

aiRthermo-package . . . 3
adiabatic_ascent . . . 4
aiRthermoConstants . . . 5
AnyAdiabaticDown . . . 6
boltonTLCL . . . 7
bruntVaisallaOmegaSquared . . . 7
C2K . . . 8
CAPE_CIN . . . 9
densityDry . . . 11
densityH2Ov . . . 12
densityMoistAir . . . 13
dewpointdepression2rh . . . 14
e2w . . . 15
equivalentPotentialTemperature . . . 15
export_constants . . . 16
export_lines . . . 17
find_lcl . . . 18
fixedlines . . . 19
gamma_saturated . . . 19
K2C . . . 20
Kindex . . . 21
latent_heat_H2O . . . 22
LIindex . . . 23
moistAdiabaticLapseRate . . . 24
moistCp . . . 25
moistCv . . . 26
parcelState . . . 26
PT2Theta . . . 27
PTheta2T . . . 28
PW . . . 29
q2e . . . 29
q2w . . . 30
RadiosondeA . . . 31
RadiosondeD . . . 32
RadiosondeDavenport . . . 33
rh2shum . . . 34
rh2w . . . 35
saturation_mixing_ratio . . . 36
saturation_pressure_H2O . . . 36
Sindex . . . 37
stuve_diagram . . . 38
TTdP2rh . . . 40
TTheta2P . . . 41
TTindex . . . 41
virtual_temperature . . . 42
w2q . . . 43

w2Td 44

Index **45**

---

aiRthermo-package *Atmospheric Thermodynamics and Visualization*

Description

Deals with many computations related to the thermodynamics of atmospheric processes. It includes many functions designed to consider the density of air with varying degrees of water vapour in it, saturation pressures and mixing ratios, conversion of moisture indices, computation of atmospheric states of parcels subject to dry or pseudoadiabatic vertical evolutions and atmospheric instability indices that are routinely used for operational weather forecasts or meteorological diagnostics.

Unless otherwise explicitly noted (boltonTLCL and stuve_diagram) all parameters to functions must be provided in the International System of Units: P in Pa, T in K and w in kg/kg.

Author(s)

Jon Sáenz, Santos J. González-Rojí, Sheila Carreno-Madinabeitia and Gabriel Ibarra-Berastegi

Maintainer: Santos J. González-Rojí <santosjose.gonzalez@ehu.eus>

Examples

```
# CAPE, CIN index
data(RadiosondeA)
aPs<-RadiosondeA[,1]*100
aTs<-C2K(RadiosondeA[,3])
aws<-RadiosondeA[,6]/1000
capeCin<-CAPE_CIN(PlowTop=98000,precoolType="adiabatic",
                  Ps=aPs,Ts=aTs,ws=aws,doLog=0,deltaP=5,
                  getLiftedBack=TRUE,upToTop=TRUE)
print(min(capeCin$CAPE))


#pdf("stuve.pdf")
stuveA<-stuve_diagram(Pres = aPs/100,Temp=aTs-273.15)
lines(capeCin$Tl-273.15,capeCin$Pl/100,col="red",lwd=2)
#dev.off()

# Adiabatic Ascent
P0<-101325
T0<-273.15
w0<-0.0025
adiabEvol<-adiabatic_ascent(P0,T0,w0,50000,5)
```

`adiabatic_ascent` *Properties of an air parcel after adiabatic ascent*

Description

A particle located at Pstart pressure (Pa), Tstart temperature (K) and wstart mixing ratio (kg/kg) ascends (pseudo)adiabatically to Pend (Pa). The evolution is computed by numerically integrating the dT/dP ordinary differential equation (ODE) using a 4th order Runge-Kutta scheme, assuming hydrostatic equilibrium and that the particle is saturated after the Lifted Condensation Level (LCL).

Usage

```
adiabatic_ascent(Pstart, Tstart, wstart, Pend, deltaP = 1)
```

Arguments

`Pstart`	Initial value for pressure (Pa).
`Tstart`	Initial value for temperature (K).
`wstart`	Initial value for mixing ratio (kg/kg).
`Pend`	End value for pressure (Pa).
`deltaP`	deltaP (Pa) represents the numerical increment used for integrating the Ordinary Differential Equation (ODE) representing the vertical evolution.

Value

The function returns a list that includes Tend (final value of temperature) and mixRatioEnd (mixing ratio of the air parcel at the end of the evolution).

`Tend`	Temperature at the end (K).
`mixRatioEnd`	Mixing ratio at the end (kg/kg).

Examples

```
P0<-101325
T0<-273.15
w0<-0.0025
adiabEvov<-adiabatic_ascent(P0,T0,w0,50000,5)
```

aiRthermoConstants *Thermodynamical Constansts*

Description

Frecuently used constants in atmospheric thermodynamics and in this package.

Usage

```
data(aiRthermoConstants)
```

Format

aiRthermoConstants is a vector that includes the constants used by many of the functions in package.

Details

The constants stored in the vector are (in SI units): the gas constant for dry air R_d and for water vapour R_v ($\frac{J}{Kkg}$), the temperature T_0 corresponding to 0 degree Celsius, es_0 used to calculate the saturated vapour pressure (Pa), 1000 hPa in Pa (P1000), the specific heat of dry air for constant pressure c_p ($\frac{J}{Kkg}$) and for constant volume c_v ($\frac{J}{Kkg}$), acceleration due to gravity at sea level g ($\frac{m}{s^2}$), our definition of a missing value MISSING_VALUE (-99999999) and epsilon ε ($\frac{R_d}{R_v}$).

The values of the constants are taken from Bohren & Albrecht (1998), and they are also consistent with those used in Petty (2008), Erukhimova & North (2009) and Davies-Jones (2009).

References

Bohren, C.F., & Albrecht, B. A. (1998). Atmospheric thermodynamics. Atmospheric thermodynamics. Publisher: New York; Oxford: Oxford University Press, 1998. ISBN: 0195099044.

Petty, G.W. (2008). A First Course in Atmospheric Thermodynamics, Sundog Publishing, Madison.

North, G. R. , Erukhimova,T. L. (2009). Atmospheric Thermodynamics, Cambridge University Press, New York.

Davies-Jones, R. (2009). On formulas for equivalent potential temperature, Monthly Weather Review, 137,3137-3148. doi:10.1175/2009MWR2774.1.

Examples

```
#Define the Rd
data(aiRthermoConstants)
Rd <- aiRthermoConstants['Rd']

#Define gravity
data(aiRthermoConstants)
g <- aiRthermoConstants['g']
```

AnyAdiabaticDown *Adiabatic Downwards Evolution*

Description

Calculation of the state of an air parcel subject to an adiabatic downwards evolution, taking into account the initial conditions of the parcel (Pstart, Tstart, wstart, wcstart).

Usage

```
AnyAdiabaticDown(Pstart, Tstart, wstart, wcstart, Pend, deltaP)
```

Arguments

Pstart	Initial pressure value (Pa).
Tstart	Initial temperature value (K).
wstart	Initial mixing ratio value (kg/kg).
wcstart	Initial mixing ratio value for the condensates (kg/kg).
Pend	Final pressure value (Pa).
deltaP	Pressure step used for the calculation. It must be a positive value (Pa).

Details

In this case, we start from a parcel at pressure pstart (Pa), temperature tstart (K) and mixing ratio wstart (kg/kg), with potentially some condensates wcstart (kg/kg). The latent heat (L) used during the evolution depends on the Temperature (T). It is computed as described by latent_heat_H2O. As the parcel goes down it could evaporate the condensates or, if no condensates are available anymore, it will go down according to a dry adiabatic evolution by means of a dry adiabatic process until the level Pend. At this point, it will have a temperature Tend, mixing ratio (vapour) Wend and Wcend (may be still some condensates could be left) using steps of pressure dP (always positive).

Value

This function returns a list including the following values:

Tend	Temperature at the end (K).
Wend	Mixing ratio of water vapour at the end (kg/kg).
Wcend	Mixing ratio of condensed water at the end (kg/kg).

Examples

```
AnyAdiabaticDown(50000,227,8.5e-5,0.005,101325,5)
AnyAdiabaticDown(70000,237,4e-4,0.005,101325,5)
```

`boltonTLCL` *Find the Temperature at the Lifting Condensation Level (LCL)*

Description

This function is used to calculate the Temperature at the Lifting Condensation Level (LCL) using Bolton's approximation instead of integrating the Ordinary Differential Equation (ODE) upwards.

Usage

```
boltonTLCL(TempCelsius, rh, consts = export_constants())
```

Arguments

`TempCelsius`	Temperature in degrees Celsius.
`rh`	Relative humidity (%).
`consts`	Includes the frecuently used constants in thermodynamics defined in *aiRthermoConstants*.

Value

This function calculates an approximation of the temperature in degrees Celsius corresponding to the LCL.

References

Bolton, D. (1980). The computation of equivalent potential temperature, Monthly Weather Review 108, 1046-1053. doi:10.1175/1520-0493(1980)108<1046:TCOEPT>2.0.CO;2.

Examples

```
T0=273.15
rh=66.25489
boltonTLCL(T0,rh)
```

`bruntVaisallaOmegaSquared`
Brunt-Vaisalla (angular) frequency (squared)

Description

Brunt-Vaisalla (angular) frequency (aquared, s^{-2}) considering hydrostatic equilibrium. P is used as a vertical level.

Usage

```
bruntVaisallaOmegaSquared(Ps, Ts, ws, consts = export_constants())
```

Arguments

Ps	A vector with pressure values (Pa).
Ts	A vector with temperature values (K).
ws	A vector with mixing ratio values (kg/kg).
consts	The constants defined in *aiRthermoConstants* data are necessary. The constants g and Rd are used.

Details

The angular frequency (squared, s^{-2}) is returned in order to avoid complex numbers.

Value

The Brunt-Vaisalla (angular) frequency (squared) is returned.

Note

For stable atmospheres, should be positive at every level. Ps, Ts and ws are 1D arrays.

See Also

PT2Theta and densityMoistAir are used inside bruntVaisallaOmegaSquared function.

Examples

```
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dTs<-C2K(RadiosondeD[,3])
dws<-RadiosondeD[,6]/1000
bruntVaisallaOmegaSquared(dPs,dTs,dws)
```

C2K *From Celsius to Kelvin degrees*

Description

This function makes the transformation from Celsius to Kelvin degrees.

Usage

```
C2K(Tc, consts = export_constants())
```

Arguments

Tc	A vector of temperatures in degrees Celsius.
consts	This funtion uses the T_0 constant, corresponding to 0 degree Celsius expressed in K (273.15 K).

Value

A vector of temperatures in Kelvin degrees is returned.

See Also

aiRthermoConstants and K2C

Examples

```
data(RadiosondeD)
dTs<-RadiosondeD[,3]
C2K(dTs)
```

CAPE_CIN *Calculation of CAPE and CIN*

Description

Taking into account the data obtained in a radiosonde, and after defining the initial values of the parcel, this function calculates the values of CAPE and CIN for the sounding.

Usage

```
CAPE_CIN(Ps, Ts, ws, deltaP = 5, P0 = NA, T0 = NA, w0 = NA, PlowTop = NA,
precoolType = "none", doLog = 0, getLiftedBack = FALSE, upToTop = TRUE,
checkBuoyancy = 0)
```

Arguments

Ps	Pressures (Pa) defining the sounding.
Ts	Temperatures (K) defining the sounding.
ws	Mixing ratios (kg/kg) defining the sounding.
deltaP	The width (Pa) of the layers used in the calculation of the numerical solution for the vertical evolution. A default value of 5 Pa is used. It must be positive.
P0	The initial pressure (Pa) for the parcel that is lifted (may be the lowest level of the sounding). Missing value is used by default.
T0	The initial temperature (K) of the parcel being lifted. Missing value is used by default.
w0	The initial mixing ratio (kg/kg) of the parcel being lifted.

PlowTop	If some layers must be averaged in the bottom of the sounding this argument provides the pressure (Pa) at the top of the layer that must be averaged in the bottom of the sounding. NA is used by default.
precoolType	If requested, an adiabatic or an isobaric precooling of the initial parcel is performed. "none" is used by default, but "adiabatic" and "isobaric" are also accepted.
doLog	Use logarithmic vertical interpolation between sounding levels if doLog=1. The default value is doLog=0.
getLiftedBack	TRUE/FALSE requests that the evolution of the lifted particle until the top level of the soundig is returned as a set of vectors for P, T and w (fields Pl, Tl and wl respectively). FALSE is used by default.
upToTop	TRUE(FALSE) requests that the lifted particle continues(stops) after the first crossing with the ambient sounding (EL) (until the sounding finishes). If TRUE, remaining negative areas above are accumulated into CIN only if the parcel becomes buoyant again in upper levels depending on the setting of *checkBuoyancy*. TRUE is used by default.
checkBuoyancy	If *checkBuoyancy* is TRUE, the computation of CAPE and CIN proceed to the top of the sounding if *upToTop* is TRUE if CAPE is larger than CIN while the parcel passes non-buoyant regions. The default value is FALSE.

Details

CAPE and CIN (J/kg) are calculated from a sounding given by 1D arrays for pressure Ps (Pa), for temperature Ts (K) and for mixing ratio ws (kg/kg).

If P_0/T_0/w_0 are provided, no low vertical averaging is done and these values are used as initial points for the parcel. Missing value is used by default for these arguments.

This function returns some error codes in field *outCode* in the return value if the computation of CAPE and CIN failed.

Value

Returns:

airStart	The real starting variable of the air parcel. It is a vector with 6 elements: P (Pa), Temp (K), w (kg/kg), theta (K), Tvirtual (K) and wsat (kg/kg). The values are computed depending on the input arguments.
cape	CAPE index (J/kg).
cin	CIN index (J/kg) as a negative number.
apLCL	Variables of the air parcel at the Lifting Condensation Level (LCL). It is returned as a vector with 6 elements: P (Pa), Temp (K), w (kg/kg), theta (K), virtualT (K) and wsat (kg/kg).
apLFC	Variables of the Level of Free Convection (LFC). If LFC is found, it is returned as a vector with six elements: P (Pa), Temp (K), w (kg/kg), theta (K), virtualT (K) and wsat (kg/kg).
apEL	End Level (EL). If EL is found, it is returned as a vector with six elements: P (Pa), Temp (K), w (kg/kg), theta (K), virtualT (K) and wsat (kg/kg).

gotLCL	TRUE/FALSE whether the LCL has been found or not.
gotLFC	TRUE/FALSE whether the LFC has been found or not.
gotEL	TRUE/FALSE whether the EL has been found or not.
Pl	Pressure (Pa) at every step of the lifted particle during its evolution. If requested by using getLiftedBack==TRUE, every step until the end of the radiosonde is returned.
Tl	Temp (K) at every step of the lifted particle during its evolution. If requested by using getLiftedBack==TRUE, every step until the end of the radiosonde is returned.
wl	Mixing-ratio of the lifted particle during its evolution. If requested by using getLiftedBack==TRUE, every step until the end of the radiosonde is returned.
Olifted	Number of elements in Pl/Tl/wl.
upToTop	Process the whole sounding even after finding the first "EL level".
outCode	The error code returned by the C routine that computes CAPE/CIN. If 0, everything has been OK!

Examples

```
data(RadiosondeA)
aPs<-RadiosondeA[,1]*100
aTs<-C2K(RadiosondeA[,3])
aws<-RadiosondeA[,6]/1000
capeCin<-CAPE_CIN(PlowTop=98000,precoolType="adiabatic",
                  Ps=aPs,Ts=aTs,ws=aws,doLog=0,deltaP=5,
                  getLiftedBack=TRUE,upToTop=TRUE)
print(min(capeCin$Tl))

#pdf("stuve.pdf")
stuveA<-stuve_diagram(Pres = aPs/100,Temp=aTs-273.15)
lines(capeCin$Tl-273.15,capeCin$Pl/100,col="red",lwd=2)
#dev.off()
```

---

densityDry *Density of Dry Air*

Description

From pressure P (Pa) and temperature Temp (K), this funtion calculates the density of dry air in kg/m^3.

Usage

```
densityDry(P, Temp, consts = export_constants())
```

Arguments

P	A vector with pressure values (Pa).
Temp	A vector with temperature values (K).
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

A vector with density of dry air values is returned (kg/m^3).

Examples

```
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dTs<-C2K(RadiosondeD[,3])
densityDry(dPs,dTs)
```

---

densityH2Ov *Density of water vapour*

Description

From pressure of water vapour Pw (Pa) and temperature Temp (K), this function calculates density of water vapour (kg/m^3).

Usage

```
densityH2Ov(Pw, Temp, consts = export_constants())
```

Arguments

Pw	A vector with pressure water vapour values (Pa).
Temp	A vector with temperature values (K).
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

A vector with density of water vapour values is returned (kg/m^3).

See Also

q2e and w2q

Examples

```
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dTs<-C2K(RadiosondeD[,3])
dws<-RadiosondeD[,6]/1000
h2oe<-q2e(dPs,w2q(dws))
densityH2Ov(h2oe,dTs)
```

`densityMoistAir` *Density of Moist Air*

Description

From pressure P (Pa) temperature Temp (K) and mixing ratio (kg/kg), this function calculates the density of moist air (kg/m^3).

Usage

```
densityMoistAir(P, Temp, w, consts = export_constants())
```

Arguments

`P`	A vector with pressure values (Pa).
`Temp`	A vector with temperature values (K).
`w`	A vector with mixing ratio values (kg/kg).
`consts`	The constants defined in *aiRthermoConstants* data are necessary.

Value

A vector with density of moist air values is returned (kg/m^3).

See Also

`virtual_temperature`

Examples

```
data(RadiosondeA)
aPs<-RadiosondeA[,1]*100
aTs<-C2K(RadiosondeA[,3])
aws<-RadiosondeA[,6]/1000
densityMoistAir(aPs,aTs,aws)
```

`dewpointdepression2rh` *Relative Humidity from the dew point depression*

Description

This function calculates the relative humidity (%) from the dew point depression (K).

Usage

```
dewpointdepression2rh(P, Temp, dpd, consts = export_constants())
```

Arguments

`P`	A vector with pressure values (Pa).
`Temp`	A vector with temperature values (K).
`dpd`	A vector with dew point depression values (K).
`consts`	The constants defined in *aiRthermoConstants* data are necessary.

Value

A vector with relative humidity (%).

See Also

`saturation_mixing_ratio` and `saturation_pressure_H2O`

Examples

```
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dTs<-C2K(RadiosondeD[,3])
dws<-RadiosondeD[,6]/1000
dTds=w2Td(dPs,dws)
dDPDs=dTs-dTds
dewpointdepression2rh(dPs,dTs,dDPDs)
```

e2w *Compute Mixing Ratio from partial pressure of water vapour*

Description

This function calculates the mixing ratio (kg/kg) from the partial vapour pressure of water vapour (Pa).

Usage

```
e2w(eh2o, P, consts = export_constants())
```

Arguments

eh2o	A vector with partial pressure of water vapour (Pa).
P	A vector with pressure (Pa) values.
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

A vector with mixing ratio values.

Examples

```
#Partial pressure of water vapour
data(RadiosondeA)
dPs<-RadiosondeA[,1]*100
dws<-RadiosondeA[,6]/1000
eh2o<-q2e(dPs,w2q(dws))
#Pressure
e2w(eh2o,dPs)
```

equivalentPotentialTemperature *Equivalent Potential Temperature*

Description

This function calculates the equivalent potential temperature (K), following the techniques used in Davies-Jones (2009).

Usage

```
equivalentPotentialTemperature(P, Temp, w, TLCL, consts = export_constants())
```

Arguments

P	The pressure (Pa) of the air parcel.
Temp	The temperature (K) of the parcel.
w	The mixing ratio (kg/kg) of the parcel.
TLCL	The temperature (K) at the Lifting Condensation Level (LCL).
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns the value of the equivalent potential temp (K).

References

Davies-Jones, R. (2009). On formulas for equivalent potential temperature. Monthly Weather Review, 137(9), 3137-3148.

See Also

PT2Theta and moistCp

Examples

```
data(RadiosondeA)
aPs<-RadiosondeA[,1]*100
aP0<-aPs[1]
aT0<-C2K(RadiosondeA[1,3])
aw0<-RadiosondeA[1,6]/1000
deltaP=1
Na=length(aPs)
Ptop=aPs[Na]
fndlcl=find_lcl(Ptop,aP0,aT0,aw0,deltaP)
TLCL=fndlcl$Tlcl
equivalentPotentialTemperature(aP0,aT0,aw0,TLCL)
```

---

export_constants *Export the constants*

Description

This function exports to R the constants frecuently used in the C part of *aiRthermo* for consistency.

Usage

```
export_constants()
```

Details

The constants stored in the vector are (in SI units): the gas constant for dry air R_d and for water vapour R_v ($\frac{J}{Kkg}$), the temperature T_0 corresponding to 0 degree Celsius, es_0 used to calculate the saturated vapour pressure (Pa), 1000 hPa in Pa (P1000), the specific heat of dry air for constant pressure c_p ($\frac{J}{Kkg}$) and for constant volume c_v ($\frac{J}{Kkg}$), acceleration due to gravity at sea level g ($\frac{m}{s^2}$), our definition of a missing value MISSING_VALUE (-99999999) and epsilon ε ($\frac{R_d}{R_v}$).

Constants are taken from Bohren & Albrecht (1998), and they are also consistent with those used in Petty (2008), Erukhimova & North (2009) and Davies-Jones (2009).

References

Bohren, C.F., & Albrecht, B. A. (1998). Atmospheric thermodynamics. Atmospheric thermodynamics. Publisher: New York; Oxford: Oxford University Press, 1998. ISBN: 0195099044.

Petty, G.W. (2008). A First Course in Atmospheric Thermodynamics, Sundog Publishing, Madison.

North, G. R. , Erukhimova,T. L. (2009). Atmospheric Thermodynamics, Cambridge University Press, New York.

Davies-Jones, R. (2009). On formulas for equivalent potential temperature, Monthly Weather Review, 137,3137-3148. doi:10.1175/2009MWR2774.1.

See Also

aiRthermoConstants

Examples

```
aiRthermoConstants<-export_constants()
```

---

export_lines *Export the lines for the thermodynamic diagram*

Description

This function exports the *fixedlines* for Stüve Diagram. It includes the data for plotting the pseudoadiabatic (adiabat_*_T), dry adiabatic (theta_*_T) and constant mixing ratio lines (wsat_*_T).

Usage

```
export_lines()
```

See Also

fixedlines

Examples

```
data(RadiosondeA)
aPs<-RadiosondeA[,1]*100
aTs<-C2K(RadiosondeA[,3])
stuveA<-stuve_diagram(Pres = aPs/100,Temp=aTs-273.15)
```

`find_lcl` *Calculation of the Lifted Condensation Level (LCL)*

Description

For a particle with initial conditions P_0, T_0 and w_0, this function performs an adiabatic vertical evolution until it gets saturated at most when Ptop is reached.

Usage

```
find_lcl(Ptop, P0, T0, w0, deltaP)
```

Arguments

`Ptop`	Maximun level pressure selected (Pa).
`P0`	Initial value of pressure (Pa).
`T0`	Initial value of temperature (K).
`w0`	Initial value of mixing ratio (kg/kg).
`deltaP`	The width (Pa) of the layers used in the calculation of the numerical solution for the vertical evolution. A default value of 5 Pa is used.

Value

Returns a list including the following values:

`Plcl`	The pressure at LCL (Pa).
`Tlcl`	The temperature at LCL (K).
`wlcl`	The mixing ratio at LCL (kg/kg).
`thetalcl`	The potential temperature at LCL (K).
`gotit`	0 or 1 whether the particle arrived or not to saturation (LCL) before arriving to Ptop.

Examples

```
Ptop=50000
P0=101325
T0=273.15
w0=0.0025
deltaP=5
rh=100*w0/saturation_mixing_ratio(P0,T0,export_constants())
fndlcl=find_lcl(Ptop,P0,T0,w0,deltaP)
```

fixedlines *Data for plotting the lines of the thermodynamic (STUVE) diagram*

Description

The vectors included in the list are: both components of the pseudoadiabatic lines (adiabatic_x_T, and adiabatic_y_T), labels of the pseudoadiabatic lines (adiabatic_z_T), both components of the dry adiabatic lines (theta_x_T and theta_y_T), both components of the constant mixing ratio lines (wsat_x_T and wsat_y_T) and their labels (wsat_z_T). The X components are provided in Celsius and the Y components in hPa.

Usage

```
data(fixedlines)
```

Details

The pseudoadiabatic lines were calculated by the authors for this R-package following pseudoadiabatic evolutions from 1050 hPa.

The dry adiabatic lines were obtained using the functions in *aiRthermo* for different initial conditions and for a fixed set of initial potential temperatures. A similar procedure was applied on the calculation of the constant mixing ratio lines, starting from different values of saturation mixing ratio.

Source

The data were calculated by the authors for this R-package.

See Also

export_lines

Examples

```
data(fixedlines)
```

gamma_saturated *Saturated Adiabat Gamma*

Description

Saturated adiabat at the points of the sounding as computed internally, considering hydrostatic balance and as $\frac{dT}{dP}$ (in pressure levels) (K/Pa).

Usage

```
gamma_saturated(Ps, Temps)
```

Arguments

Ps	A vector with pressure values (Pa).
Temps	A vector with temperature values (K).

Value

This function returns the vertical derivate $\Gamma_s = \frac{dT}{dP}\Big|_s$ for a saturated adiabatic evolution.

Examples

```
data(RadiosondeA)
aPs<-RadiosondeA[,1]*100
aTs<-C2K(RadiosondeA[,3])
gamma_saturated(aPs,aTs)
```

K2C *From Kelvin to Celsius degrees*

Description

This function makes the transformation from Kelvin degrees to Celsius.

Usage

```
K2C(Tk, consts = export_constants())
```

Arguments

Tk	A vector of temperatures in Kelvin degrees.
consts	This function uses the T_0 constant corresponding to 0 degree Celsius as K.

Value

This function returns a vector of temperatures in Celsius degrees.

See Also

aiRthermoConstants and C2K

Examples

```
data(RadiosondeD)
dTs<-RadiosondeD[,3]
K2C(C2K(dTs))
```

Kindex *K Instability Index*

Description

This function calculates the K instability index (Celsius) from a sounding given by the measured arrays pressure Ps (Pa) temperature Ts (K) and mixing ratio ws (kg/kg).

Usage

```
Kindex(Ps, Ts, ws, doLog = 0)
```

Arguments

Ps	A vector with pressure values (Pa) measured by the radiosonde.
Ts	A vector with temperature values (K) measured by the radiosonde.
ws	A vector with mixing ratio values (kg/kg) measured by the radiosonde.
doLog	Use logarithmic vertical interpolation between sounding levels. The default value is 0.

Details

If needed levels (850, 700 and 500 hPa) are not found in the input sounding (without extrapolation), the function returns -99999999.

Use/do not use logarithmic interpolation in pressure (if needed because mandatory levels such as 700 hPa or 500 hPa are not given in the sounding) when finding the requested levels.

Value

This function returns the K index.

Examples

```
data(RadiosondeA)
aPs<-RadiosondeA[,1]*100
aTs<-C2K(RadiosondeA[,3])
aws<-RadiosondeA[,6]/1000
aK<-Kindex(aPs,aTs,aws,0)

data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dTs<-C2K(RadiosondeD[,3])
dws<-RadiosondeD[,6]/1000
dK<-Kindex(dPs,dTs,dws,0)
```

`latent_heat_H2O` *Latent heat of vaporization or sublimation of water*

Description

This function calculates the latent heat of vaporization or sublimation of water depending as a function of temperature. It uses a polynomial approximation over water or ice.

Usage

```
latent_heat_H2O(Temps)
```

Arguments

`Temps`	A vector with temperature values (K).

Details

Taking into account the observed values in tables from Rogers and Yau (1989) and Feistel and Wagner (2006), a polynomial model is used to calculate the latent heat at different temperatures.

Value

This function returns the latent heat of vaporization or sublimation of water.

References

Rogers, R. R., and Yau, M. K. (1989). A Short Course in Cloud Physics, 3rd Edition, Pergamon Press, Oxford.

Feistel, R. and Wagner, W. (2006). A new equation of state for H2O ice Ih, Journal of Physical and Chemical Reference Data 35 1021-1047. doi:10.1063/1.2183324.

Examples

```
data(RadiosondeA)
aTs<-C2K(RadiosondeA[,3])
latent_heat_H2O(aTs)
```

LIindex *Lifted index*

Description

This function calculates the instability parameter Lifted index (Celsius) from pressure, temperature and mixing ratio values described by a vertical sounding.

Usage

```
LIindex(Ps, Ts, ws, Psurface, deltaP, PWIDTH, doLog = 0)
```

Arguments

Ps	Pressure (Pa) of the sounding.
Ts	Temperature (K) of the sounding.
ws	Mixing ratio (kg/kg) of the sounding.
Psurface	Surface pressure (Pa). If not available, the first level of the sounding can be used.
deltaP	The width (Pa) of the layers used in the numerical solution of the vertical evolution (integration of the ODE). A default value of 5 Pa is used. It must be positive.
PWIDTH	PWIDTH represents the width (Pa) of the lower layer that will be averaged for P, T and w in order to calculate a "mixed-layer" average parcel that will be used for the vertical evolution. Typically 5000-10000 Pa are used.
doLog	Use logarithmic vertical interpolation between sounding levels if doLog=1. It is not used by default (doLog=0).

Details

If the 500 hPa needed level is not exactly found in the input sounding, logarithmic/linear vertical interpolation is run to get the corresponding T/w from the Ps/Ts/ws depending on the value of doLog 0/1.

The evolution of the lifted particle is computed by integrating the dT/dP ordinary differential equation (applying the Runge-Kutta 4th order method), that represents the vertical adiabatic evolution from the initial condition to 500 hPa using a pressure step deltaP (Pa). The vertical adiabatic evolution is either dry (before saturation) or pseudoadiabatic at every vertical step with a correction for moisture in c_p using the value of the mixing ratio (c_{pm} as in Tsonis, eq 7.11).

If the sounding does not enclose the needed level of 500 hPa and the interpolation fails, the function returns -99999999.

Value

This function returns the LI index (Celsius).

References

Tsonis, A. A. (2002). An Introduction to Atmospheric Thermodynamics, Cambridge University Press, Cambridge. Eq. 7.11.

Examples

```
data(RadiosondeA)
aPs<-RadiosondeA[,1]*100
aTs<-C2K(RadiosondeA[,3])
aws<-RadiosondeA[,6]/1000
LIindex(aPs,aTs,aws,max(aPs),5,2500,0)
```

`moistAdiabaticLapseRate`

Moist Adiabatic Lapse Rate

Description

This function calculates the moist adiabatic lapse rate according to a provided mixing ratio (kg/kg) (Tsonis, eq 7.29).

Usage

```
moistAdiabaticLapseRate(w, consts = export_constants())
```

Arguments

`w`	A vector with mixing ratio values (kg/kg).
`consts`	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns a vector with the moist adiabatic lapse rate (dry adiabatic lapse rate with correction of c_p due to the water vapour in moist air).

References

Tsonis, A. A. (2002). An Introduction to Atmospheric Thermodynamics, Cambridge University Press, Cambridge. Eq. 7.29.

Examples

```
data(RadiosondeA)
aws<-RadiosondeA[,6]/1000
moistAdiabaticLapseRate(aws)
```

`moistCp` *Moist Cp*

Description

This function corrects the value of dry c_p due to the existence of water vapour acording to equation 7.11 from Tsonis (2002).

Usage

```
moistCp(w, consts = export_constants())
```

Arguments

`w`	A vector with mixing ratio values (kg/kg).
`consts`	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns the value of dry c_p corrected by the mixing ratio.

References

Tsonis, A. A. (2002). An Introduction to Atmospheric Thermodynamics, Cambridge University Press, Cambridge. Eq. 7.11.

See Also

`w2q` and `moistCv`

Examples

```
data(RadiosondeD)
dws<-RadiosondeD[,6]/1000
moistCp(dws)
```

moistCv *Moist cv value*

Description

This function is similar to moistCp but for c_v. In this case, it is the value of c_v corrected due to the existence of water vapour (equation 7.12) from Tsonis (2002).

Usage

```
moistCv(w, consts = export_constants())
```

Arguments

w	A vector with mixing ratio values (kg/kg).
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns the value of c_v corrected due to the existence of water vapour.

References

Tsonis, A. A. (2002). An Introduction to Atmospheric Thermodynamics, Cambridge University Press, Cambridge. Eq. 7.12.

See Also

w2q and moistCp

Examples

```
data(RadiosondeD)
dws<-RadiosondeD[,6]/1000
moistCv(dws)
```

parcelState *State of a parcel*

Description

The function calculates the state of a parcel for easier computations.

Usage

```
parcelState(Press, Temp, w = 0, consts = export_constants())
```

Arguments

Press	Value of pressure (Pa) of the parcel.
Temp	Value of temperature (K) of the parcel.
w	Value of mixing ratio (kg/kg) of the parcel.
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns a list including the following values:

pressure	Pressure value (Pa).
temperature	Temperature value (K).
mixingratio	Mixing ratio value (kg/kg).
theta	Potential temperature value (K).
virtualTemp	Virtual temperature value (K).
saturationMixingRatio	Saturation mixing ratio value (kg/kg).

See Also

PT2Theta, virtual_temperature and saturation_mixing_ratio

Examples

```
parcelState(101325,273.15,0.2)
```

PT2Theta *Potential Temperature from pressure and temperature*

Description

This function calculates the potential temperature from given temperature and pressure.

Usage

```
PT2Theta(P, Temp, w = 0, consts = export_constants())
```

Arguments

P	A vector with pressure values (Pa).
Temp	A vector with temperature values (K).
w	A vector with mixing ratio values (kg/kg). Default value 0.
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns a vector with potencial temperature. Mixing ratio is only used to correct the value of c_p, not to calculate a moist adiabatic evolution.

See Also

moistCp

Examples

```
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dTs<-C2K(RadiosondeD[,3])
dThetas=PT2Theta(dPs,dTs)
```

PTheta2T *Temperature from pressure and potential temperature*

Description

This function calculates the temperature from a given pressure and potential temperature.

Usage

```
PTheta2T(P, Theta, w = 0, consts = export_constants())
```

Arguments

P	A vector with pressure values (Pa).
Theta	A vector with potential temperature (K).
w	A vector with mixing ratio values (kg/kg). Default value 0.
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns a vector with temperatures (K).

See Also

moistCp

Examples

```
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dTs<-C2K(RadiosondeD[,3])
dThetas=PT2Theta(dPs,dTs)
PTheta2T(dPs,dThetas)
```

PW *Vertically integrated water vapour column*

Description

This function calculates the vertically integrated water vapour column integrating in pressure vertical coordinates.

Usage

```
PW(w, PRES, Psurf, consts = export_constants())
```

Arguments

w	A vector with mixing ratio values of a sounding (kg/kg).
PRES	A vector with pressure values of a sounding (Pa).
Psurf	Is the mean sea level pressure at the place of a sounding (Pa).
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns the vertically integrated water vapour column.

Examples

```
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dws<-RadiosondeD[,6]/1000
PW(dws,dPs,dPs[1])
```

q2e *Partial Vapour Pressure*

Description

This function calculates the partial vapour pressure from specific humidity.

Usage

```
q2e(P, q, consts = export_constants())
```

Arguments

P	A vector with pressure values (Pa).
q	A vector with specific humidity values (kg/kg).
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns the value of the partial vapour pressure (Pa).

Examples

```
# Get partial pressure of water vapour
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dws<-RadiosondeD[,6]/1000
h2oe<-q2e(dPs,w2q(dws))
```

---

q2w *Water vapour mixing Ratio to specific humidity*

Description

This function calculates the water vapour mixing ratio (kg/kg) from specific humidity (kg/kg).

Usage

```
q2w(q)
```

Arguments

q	A vector with specific humidity values (kg/kg).

Value

This function returns a vector with mixing ratio values in kg/kg.

Examples

```
data(RadiosondeD)
dws<-RadiosondeD[,6]/1000
q2w(w2q(dws))
```

RadiosondeA *Radiosonde A*

Description

Contains the information measured by a sounding in Santander (Station 08023) in 2010, June 16th at 12:00 UTC. It was not a really unstable day but a great amount of (large scale) precipitation was measured.

Usage

```
data("RadiosondeA")
```

Format

A data frame with 74 observations on the following 11 variables.

`V1` a vector with pressure values (hPa).

`V2` a vector with height (m).

`V3` a vector with temperature values (Celsius).

`V4` a vector with dew point temperature values (Celsius).

`V5` a vector with relative humidity values (%).

`V6` a vector with mixing ratio values (g/kg).

`V7` a vector with wind direction values (degrees).

`V8` a vector with wind speed values (knots).

`V9` a vector with potential temperature (K).

`V10` a vector with equivalent potential temperature (K).

`V11` a vector with virtual potential temperature (K).

See Also

RadiosondeD and RadiosondeDavenport

Examples

```
data(RadiosondeA)
#Calculate the pressure in Pa
RadiosondeA$V1*100

#Calculate the temperature in K
C2K(RadiosondeA$V3)
```

RadiosondeD *Radiosonde D*

Description

Contains the information measured by a sounding in Barcelona (station 05190) in 2013, August 7th at 12:00 UTC. According to the university of Wyoming, the CAPE was higher than 3000 J/kg and a great amount of (convective) precipitation was measured.

Usage

```
data("RadiosondeD")
```

Format

A data frame with 70 observations on the following 11 variables.

`V1` a vector with pressure values (hPa).

`V2` a vector with height (m).

`V3` a vector with temperature values (Celsius).

`V4` a vector with dew point temperature values (Celsius).

`V5` a vector with relative humidity values (%).

`V6` a vector with mixing ratio values (g/kg).

`V7` a vector with wind direction values (degrees).

`V8` a vector with wind speed values (knots).

`V9` a vector with potential temperature (K).

`V10` a vector with equivalent potential temperature (K).

`V11` a vector with virtual potential temperature (K).

See Also

`RadiosondeA` and `RadiosondeDavenport`

Examples

```
data(RadiosondeD)
#Calculate the pressure in Pa
RadiosondeD$V1*100

#Calculate the temperature in K
C2K(RadiosondeD$V3)
```

RadiosondeDavenport *Radiosonde Davenport*

Description

Contains the information measured by a sounding in Davenport (station 74455) in 1997, June 21st at 00:00 UTC. That day was a very unstable situation.

Usage

```
data("RadiosondeDavenport")
```

Format

A data frame with 67 observations on the following 11 variables.

`V1` a vector with pressure values (hPa).

`V2` a vector with height (m).

`V3` a vector with temperature values (Celsius).

`V4` a vector with dew point temperature values (Celsius).

`V5` a vector with relative humidity values (%).

`V6` a vector with mixing ratio values (g/kg).

`V7` a vector with wind direction values (degrees).

`V8` a vector with wind speed values (knots).

`V9` a vector with potential temperature (K).

`V10` a vector with equivalent potential temperature (K).

`V11` a vector with virtual potential temperature (K).

See Also

RadiosondeA and RadiosondeD

Examples

```
data(RadiosondeDavenport)
#Calculate the pressure in Pa
RadiosondeDavenport$V1*100

#Calculate the temperature in K
C2K(RadiosondeDavenport$V3)
```

rh2shum *Specific Humidity from relative humidity*

Description

This function calculates the specific humidity from a given relative humidity.

Usage

```
rh2shum(P, Temp, rh, consts = export_constants())
```

Arguments

P	A vector with pressure values (Pa).
Temp	A vector with temperature values (Kelvin).
rh	A vector with relative humidity values (%).
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns a vector with specific humidity (kg/kg).

See Also

rh2shum

Examples

```
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dTs<-C2K(RadiosondeD[,3])
dws<-RadiosondeD[,6]/1000
dTds<-w2Td(dPs,dws)
rhs<-TTdP2rh(dTs,dTds,dPs)
rh2shum(dPs,dTs,rhs)
```

rh2w *Mixing Ratio from relative humidity*

Description

This function gets the mixing ratio (kg/kg) from a given relative humidity (%), pressure (Pa) and temperature (K).

Usage

```
rh2w(P, Temp, rh, consts = export_constants())
```

Arguments

P	A vector with pressure values in Pa.
Temp	A vector with temperature values in Kelvin.
rh	A vector with relative humidity values in (%).
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns a vector with mixing ratio values (kg/kg).

See Also

saturation_mixing_ratio

Examples

```
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dTs<-C2K(RadiosondeD[,3])
dws<-RadiosondeD[,6]/1000
dTds<-w2Td(dPs,dws)
rhs<-TTdP2rh(dTs,dTds,dPs)
wfromrh<-rh2w(dPs,dTs,rhs)
```

saturation_mixing_ratio

Saturation Mixing Ratio

Description

This function calculates the saturation mixing ratio from a given temperature and pressure.

Usage

```
saturation_mixing_ratio(P, Temp, consts = export_constants())
```

Arguments

P	A vector with pressure values in Pa.
Temp	A vector with temperature values in Kelvin.
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns a vector with saturation mixing ratio values (kg/kg).

Examples

```
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dTs<-C2K(RadiosondeD[,3])
saturation_mixing_ratio(dPs,dTs)
```

saturation_pressure_H2O

Saturation Pressure

Description

This function returns the saturation pressure (Pa) from a given array of temperatures (K). It uses approximate equations 5.67 and 5.70 in Bohren Albrecht, 1998.

Usage

```
saturation_pressure_H2O(Temps)
```

Arguments

Temps	A vector with temperature values in Kelvin.

Details

Saturation pressure of water vapour e_s is computed over ice/water depending whether the temperature is over/under 273.15 K (0 degree Celsius) at every element of the array.

Value

This function returns a vector with saturation pressure values (Pa).

References

Bohren, C.F., & Albrecht, B. A. (1998). Atmospheric thermodynamics. Atmospheric thermodynamics. Publisher: New York; Oxford: Oxford University Press, 1998. ISBN: 0195099044. Equations 5.67 and 5.70.

Examples

```
data(RadiosondeA)
aTs<-C2K(RadiosondeA[,3])
esats<-saturation_pressure_H2O(aTs)
```

Sindex *Showalter Instability Index*

Description

This function computes Showalter instability index (Celsius) from given parameters from a vertical sounding pressure (Pa), temperature (K) and mixing ratio (kg/kg).

Usage

```
Sindex(Ps, Ts, ws, deltaP, doLog = 0)
```

Arguments

Ps	A vector with pressure values in Pa.
Ts	A vector with temperature values in Kelvin.
ws	A vector with mixing ratio values in kg/kg.
deltaP	The width (Pa) of the layers used in the numerical solution of the vertical evolution.
doLog	Use logarithmic vertical interpolation between sounding levels. A default value is 0.

Details

If the needed levels (850 hPa or 500 hPa) are not exactly found in the input sounding, logarithmic/linear vertical interpolation is run to get the corresponding T/w from the Ps/Ts/ws depending on the value of doLog (TRUE or FALSE).

The evolution of the lifted particle is computed by integrating the dT/dP ordinary differential equation (applying the Runge Kutta 4th order method) that represents the vertical adiabatic evolution from 850 hPa to 500 hPa using a pressure step dP > 0 (Pa). The vertical adiabatic evolution is either dry (before saturation) or pseudoadiabatic at every vertical step with a correction for moisture in the specific heat at constant pressure c_p during the dry steps (as in Tsonis, eq 7.11).

If the sounding does not enclose the needed levels and the interpolation fails, the function returns -99999999.

Value

This function returns the Showalter instability index (Celsius).

References

Djuric D. (1994). Weather Analysis, Prentice Hall, New Jersey.

See Also

LIindex

Examples

```
data(RadiosondeA)
aPs<-RadiosondeA[,1]*100
aTs<-C2K(RadiosondeA[,3])
aws<-RadiosondeA[,6]/1000
S<-Sindex(aPs,aTs,aws,5,0)
```

---

stuve_diagram *Thermodynamic (STUVE) Diagram*

Description

This function generates an Stüve diagram.

Usage

```
stuve_diagram(Pres, Temp, TempD = NA, XLIM = c(-80, 45), YLIM = c(1050, 100),
col.lines = NULL, lty.lines = NULL, lwd.lines = NULL)
```

Arguments

Pres	A vector with pressure values in hPa.
Temp	A vector with temperature values in Celsius .
TempD	An optional vector with dew point temperatures in Celsius. The default value is NA.
XLIM	X axis limit in Celsius. Default value is c(-80, 45).
YLIM	Y axis limit in hPa. Default value is c(1050, 100).
col.lines	A vector of colours for the stuve_diagram lines. They must be provided in this order: isotherms, isobars, dry adiabats, moist adiabats, constant mixing ratio lines and sounding. Default colours are c("grey", "grey", "olivedrab", "olivedrab", "brown", "red").
lty.lines	A vector of line-types for the stuve_diagram. They must be provided following the same order as for the col.lines argument. Default values are c("dotted", "dotted", "dotted", "solid", "dotted", "solid").
lwd.lines	A vector of line-widths for the stuve_diagram. They must be provided following the same order as for the col.lines and lty.lines arguments. Default values are c(2,2,2,1,2,1).

Details

It is possible to add extra lines and to save as a pdf, jpeg or png (see examples).

Value

The result is a plot object.

Examples

```
data(RadiosondeA)
aPs<-RadiosondeA[,1]*100
aTs<-C2K(RadiosondeA[,3])
aws<-RadiosondeA[,6]/1000
capeCin<-CAPE_CIN(PlowTop=98000,precoolType="adiabatic",
                  Ps=aPs,Ts=aTs,ws=aws,doLog=0,deltaP=5,
                  getLiftedBack=TRUE,upToTop=TRUE)

#How to add a line to the plot
stuveA<-stuve_diagram(Pres = aPs/100,Temp=aTs-273.15)
lines(capeCin$Tl-273.15,capeCin$Pl/100,col="blue",lwd=2)
```

TTdP2rh *Relative Humidity from temperature, pressure and dew point temperature*

Description

This function calculates the relative humidity from given temperature, dew point temperature and pressure.

Usage

```
TTdP2rh(Temp, Td, P, consts = export_constants())
```

Arguments

Temp	A vector with temperature values in Kelvin.
Td	A vector with dew point temperature in Kelvin.
P	A vector with pressure values in Pa.
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns a vector with relative humidity values.

See Also

saturation_mixing_ratio

Examples

```
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dTs<-C2K(RadiosondeD[,3])
dws<-RadiosondeD[,6]/1000
dTds<-w2Td(dPs,dws)
rhs<-TTdP2rh(dTs,dTds,dPs)
```

TTheta2P *Pressure from temperature and potential temperature*

Description

This function calculates the pressure from given potential temperature and temperature, assuming a dry adiabatic evolution (mixing ratio is only used to correct the values of c_p).

Usage

```
TTheta2P(Temp, Theta, w = 0, consts = export_constants())
```

Arguments

Temp	A vector with temperature values in Kelvin.
Theta	A vector with potential temperature values in Kelvin.
w	Initial value of mixing ratio (kg/kg). By default 0.
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns a vector with pressure values.

Examples

```
 data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dTs<-C2K(RadiosondeD[,3])
dws<-RadiosondeD[,6]/1000
dTds<-w2Td(dPs,dws)
dThetas<-PT2Theta(dPs,dTs)
TTheta2P(dTs,dThetas)
```

TTindex *Total-Totals Instability Index*

Description

Total-Totals instability index (Celsius) from parameters (1D arrays) Ps (pressure, Pa) Ts (temperature, Kelvin) and ws (mixing ratio, kg/kg) obtained from a vertical sounding.

Usage

```
TTindex(Ps, Ts, ws, doLog = 0)
```

Arguments

Ps	A vector with pressure values in Pa.
Ts	A vector with temperature values in Kelvin.
ws	A vector with mixing ratio values in kg/kg.
doLog	Use logarithmic vertical interpolation between sounding levels. A default value is 0.

Details

If the needed levels (850 hPa or 500 hPa) are not exactly found in the input sounding, logarithmic/linear vertical interpolation is run depending on the value of doLog (TRUE or FALSE).

If the sounding does not enclose the needed levels and the interpolation fails, the function returns -99999999.

Value

This function returns the Total-Totals instability index (Celsius).

Examples

```
data(RadiosondeDavenport)
aPs<-RadiosondeDavenport[,1]*100
aTs<-C2K(RadiosondeDavenport[,3])
aws<-RadiosondeDavenport[,6]/1000
aTT<-TTindex(aPs,aTs,aws,0)
```

---

virtual_temperature *Virtual Temperature*

Description

This function calculates the virtual temperature from given pressure and mixing ratio.

Usage

```
virtual_temperature(P, Temp, w, consts = export_constants())
```

Arguments

P	A vector with pressure values in Pa.
Temp	A vector with temperature values in Kelvin.
w	A vector with mixing ratio values in kg/kg.
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns a vector with virtual temperature values.

See Also

q2e

Examples

```
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dTs<-C2K(RadiosondeD[,3])
dws<-RadiosondeD[,6]/1000
virtual_temperature(dPs,dTs,dws)
```

---

w2q *Specific Humidity from mixing ratio*

Description

This function calculates the specific humidity from a given Water mixing ratio.

Usage

```
w2q(w)
```

Arguments

w	A vector with mixing ratio values in kg/kg.

Value

The function returns a vector with the specific humidity.

Examples

```
data(RadiosondeD)
dws<-RadiosondeD[,6]/1000
w2q(dws)
```

w2Td *Dew point temperature from mixing ratio*

Description

This function calculates the dew point temperature from given mixing ratio and pressure, following the APPROXIMATE expression 5.68 in Bohren and Albrech (1998).

Usage

```
w2Td(P, w, consts = export_constants())
```

Arguments

P	A vector with pressure values in Pa.
w	A vector with mixing ratio (kg/kg).
consts	The constants defined in *aiRthermoConstants* data are necessary.

Value

This function returns a vector with the dew point temperature.

References

Bohren, C.F., & Albrecht, B. A. (1998). Atmospheric thermodynamics. Atmospheric thermodynamics. Publisher: New York; Oxford: Oxford University Press, 1998. ISBN: 0195099044. Equation 5.68.

Examples

```
data(RadiosondeD)
dPs<-RadiosondeD[,1]*100
dws<-RadiosondeD[,6]/1000
w2Td(dPs,dws)
```

Index

∗ **Datasets**
aiRthermoConstants, 5
fixedlines, 19
RadiosondeA, 31
RadiosondeD, 32
RadiosondeDavenport, 33
∗ **Functions**
adiabatic_ascent, 4
AnyAdiabaticDown, 6
boltonTLCL, 7
bruntVaisallaOmegaSquared, 7
C2K, 8
CAPE_CIN, 9
densityDry, 11
densityH2Ov, 12
densityMoistAir, 13
dewpointdepression2rh, 14
e2w, 15
equivalentPotentialTemperature, 15
export_constants, 16
export_lines, 17
find_lcl, 18
gamma_saturated, 19
K2C, 20
Kindex, 21
latent_heat_H2O, 22
LIindex, 23
moistAdiabaticLapseRate, 24
moistCp, 25
moistCv, 26
parcelState, 26
PT2Theta, 27
PTheta2T, 28
PW, 29
q2e, 29
q2w, 30
rh2shum, 34
rh2w, 35
saturation_mixing_ratio, 36
saturation_pressure_H2O, 36
Sindex, 37
stuve_diagram, 38
TTdP2rh, 40
TTheta2P, 41
TTindex, 41
virtual_temperature, 42
w2q, 43
w2Td, 44
∗ **Package**
aiRthermo-package, 3

adiabatic_ascent, 4
aiRthermo *(*aiRthermo-package*)*, 3
aiRthermo-package, 3
aiRthermoConstants, 5, *9*, *17*, *20*
AnyAdiabaticDown, 6

boltonTLCL, *3*, 7
bruntVaisallaOmegaSquared, 7

C2K, 8, *20*
CAPE_CIN, 9

densityDry, 11
densityH2Ov, 12
densityMoistAir, *8*, 13
dewpointdepression2rh, 14

e2w, 15
equivalentPotentialTemperature, 15
export_constants, 16
export_lines, 17, *19*

find_lcl, 18
fixedlines, *17*, 19

gamma_saturated, 19

K2C, *9*, 20
Kindex, 21

latent_heat_H2O, *6*, 22
LIindex, 23, *38*

moistAdiabaticLapseRate, 24
moistCp, *16*, 25, *26*, *28*
moistCv, *25*, 26

parcelState, 26
PT2Theta, *8*, *16*, 27, *27*
PTheta2T, 28
PW, 29

q2e, *12*, 29, *43*
q2w, 30

RadiosondeA, 31, *32, 33*
RadiosondeD, *31*, 32, *33*
RadiosondeDavenport, *31, 32*, 33
rh2shum, 34, *34*
rh2w, 35

saturation_mixing_ratio, *14*, *27*, *35*, 36, *40*
saturation_pressure_H2O, *14*, 36
Sindex, 37
stuve_diagram, *3*, 38

TTdP2rh, 40
TTheta2P, 41
TTindex, 41

virtual_temperature, *13*, *27*, 42

w2q, *12*, *25, 26*, 43
w2Td, 44